Thermoid®

PILE DRIVER STEAM

The Pile Driver Steam hose is recommended for applications that require saturated steam service up to +388°F on driving systems. It features an EPDM tube that is specifically compounded to resist permeation and prevent premature failure. The multiple plies of tire cord with plated steel cable reinforcement enable this hose to maintain a working pressure of 200 psi, regardless of hose size.



RESISTANCE BRANDING 00

Thermoid HBD Industries
Pile Driver Steam Hose 200 PSI
WP Serial Number Made In USA

Cover Color: Black **Oil Resistance:** Limited

Construction:

Tube: EPDM, also available in CR for oil resistance
Cover: EPDM, also available in CR for oil resistance
Reinforcement: Multiple plies of tire cord and plated steel cable
sperature Range: Saturated steam service to +388°F (+198°C)

Temperature Range: Packaging:

100 ft. maximum Minimum order 300 ft.

Product Number	Nominal I.D. (inches) (mm)		Nominal O.D. (inches) (mm)		Plies	Working (psi)	Pressure (Mpa)	Min. Ben (inches)	nd Radius (mm)	We (lb/ft)	ight (Kg/m)
34854634002▲	2	50.80	3.13	79.38	4	200	1.38	20.00	508.00	4.10	6.10
34854636002▲	2-1/2	63.50	3.38	85.73	4	200	1.38	25.00	635.00	5.40	8.04
34854638002▲	3	76.20	4.50	114.30	4	200	1.38	30.00	762.00	6.40	9.52
34854640002▲	4	101.60	5.63	142.88	4	200	1.38	40.00	1016.00	9.30	13.84
34854642002▲	6	152.40	7.81	198.44	6	200	1.38	60.00	1524.00	18.60	27.68

▲ = Make To Order (MTO)

ALERT: Large size, industrial hoses have caution and/or safety usage printed information attached by tag to the product or this information is printed onto the hose.